PERFORMANCE IN LIGHTING



JOLLY 1 S/W



















Range of wall-mount floodlights, in two sizes, comprising:

Polyester powder-painted die-cast aluminium housing

Flat tempered glass diffuser

Extra pure polished aluminium reflectors

Anti-aging silicone gasket

Cable entry through tear-proof cable clamp PG11 for cables Ø 5 - Ø 10 mm (for small dimensions), or tear-proof cable clamp M20x1.5 for cables for cables Ø 10 - Ø 14 mm (for large dimensions)

Stainless steel external screws

Fully integrated stainless steel aluminium spring clips

Powder coated steel bracket



| Lampholder | Watt | ILCOS | LBS | Colour | Insulation class | €₹ | KELVIN | Optical type | Optic beam | Code |
|------------|-------|-------|------------------|----------------|------------------|----|--------|--------------|------------|----------|
| RX7S | 1X70 | SD-MD | HST-DE-MF-HIT-DE | GREY ALUMINIUM | I | - | - | S/W | - | 05208694 |
| RX7S | 1X150 | SD-MD | HST-DE-MF-HIT-DE | GREY ALUMINIUM | I | - | - | S/W | - | 05208794 |
| RX7S | 1X150 | MD | HIT-DE | GREY ALUMINIUM | I | - | 4200 | S/W | - | 07023094 |
| RX7S | 1X70 | MD | HIT-DE | GREY ALUMINIUM | I | - | 4200 | S/W | - | 07023194 |